



PRELIMINARY

C 700 V2 BLUOS STREAMING AMPLIFIER

BluOS™ HybridDigital



NAD C 700 V2 BLUOS STREAMING AMPLIFIER

The C 700 V2 BluOS Streaming Amplifier is a compact, high-value all-in-one sound system that builds upon the success of its predecessor with an upgraded DAC, enhanced connectivity, expanded output capabilities, more control options, and even more advanced processing.

At its heart, the personality of this just-add-speakers powerhouse remains unchanged. Inside the solid aluminum case is a dynamic HybridDigital UcD amplifier and BluOS-enabled network streamer. Using the intuitive BluOS app on your smartphone, tablet, PC, or Mac, you can access music from your personal digital library or stream from online services such as Spotify, Amazon Music Ultra HD, Tidal, Qobuz and many more. The C 700 V2 can operate on its own or as part of a whole-home BluOS music ecosystem. But that's just scratching the surface.

NEW FOR V2

The C 700 V2 takes its "all-in-one" ethos to new heights, thanks to the addition of a phono stage (MM) and the ability to expand the C 700 V2's output beyond 2- or 2.1-channel stereo. Thanks to the power of the BluOS platform, it's easy to add a pair of wireless BluOS-Enabled players, in addition to a wired subwoofer, for a full 4.1-channel home cinema experience, complete with Dolby Digital processing.

The C 700 V2 is Dirac Ready* to support the optional Dirac Live room correction. Simply purchase and activate a Dirac Live license and use a calibrated microphone (sold separately) to measure the response of your room, and you'll now be able to enjoy music and movies from the C 700 V2 as intended, with perfectly tuned bass and enhanced clarity. The C 700 V2 can store up to five Dirac profiles for different sources or seating arrangements and room conditions, any of which can be recalled with the touch of a button on the included BC1 IR remote control.

Following menus on the C 700 V2's colour display, you can adjust amplifier settings with the control knob and navigation buttons on the front panel. And the C 700 V2 can learn commands from your favourite remote control.

FEATURES & DETAILS

- HybridDigital UcD amplifier with 2x80 Watts of continuous power into 8 or 4 ohms and 2x120 Watts of instantaneous power
- Solid aluminum body and 5" high-definition colour glass display
- Audiophile-grade ESS ES9028 Sabre DAC chip
- Dedicated MM phono input and line level input
- Add BluOS Enabled Players, along with a sub, for a complete 4.1-channel home-theatre experience
- Dolby Digital decoding
- Dirac Ready*
- IR remote control
- Works with intuitive BluOS Controller app for Android, iOS, macOS, and Windows
- MQA decoding and rendering
- BluOS multi-room streaming to 64 zones, with integrated support for over 20 streaming services and thousands of internet radio stations
- Lossless and high-resolution streaming (up to 24-bit/192kHz) from Amazon Music Ultra HD, Tidal, Qobuz, Deezer, and Idagio
- Support for Apple AirPlay 2, Spotify Connect, and Tidal Connect
- Voice control via Amazon Alexa, Apple Siri
- HDMI eARC, optical and coaxial digital inputs
- USB Type-A port for connecting an external drive, Dirac Ready measurement microphone
- Wi-Fi and Gigabit Ethernet
- Two-way aptX HD Bluetooth
- 12V Trigger output and IR remote sensor input
- Available drivers for Control4, Crestron, Elan, RTI, and other smart home control systems



A FEAST FOR ALL YOUR SENSES

Thanks to its elegant, minimalist design and premium materials, the C 700 V2 is as easy on the eyes as it is on the ears. Its sleek front panel houses a 5" glass high-definition colour screen that displays album art, track progress, and system settings. Following the menus on the C 700 V2's display, you can easily adjust the unit's configuration or navigate your favourite music with the included remote control or the front-panel control knob and navigation buttons.

Employing NAD's proven HybridDigital UcD amplifier technology, the C 700 V2 can deliver 2x80 watts of continuous power and 2x120 watts of instantaneous power, for effortless reproduction of musical transients with ultra-low noise and brilliant dynamics.

THOROUGHLY MODERN INSIDE AND OUT

With built-in Ethernet and Wi-Fi, and the award-winning BluOS software platform, the C 700 V2 has everything you need to play music through your favourite speakers. You can use the BluOS Controller app to select tunes from internet radio and over 20 different streaming services, or play music stored on an external drive connected to the C 700 V2's USB port.

Spotify Connect and Tidal Connect are included so you can control playback from the apps for those services; AirPlay 2 allows you to stream music from Apple devices and iTunes libraries. You can search for music that fits your mood using nothing but the power of your voice, thanks to support for Amazon Alexa and Apple Siri.

Like all BluOS-enabled components, the C 700 V2 has full MQA decoding and rendering capabilities. Its upgraded ESS Sabre ES9028 DAC will redefine your listening experience with unparalleled precision and breathtaking clarity. Whether listening to classical symphonies, modern rock, or blockbuster movies, the C 700 V2 unveils hidden layers of sound and delivers all the nuances of your high-resolution music streams, up to 24-bit/192kHz, from services such as Amazon Music Ultra HD, Qobuz, Tidal and more.

CONTROL AND CONNECT

The C 700 V2 has a Moving Magnet phono stage in addition to a stereo RCA analogue audio input, as well as coaxial and optical digital inputs, for connecting disc players, game consoles, media adapters, and other components. There's also an HDMI eARC port for connecting compatible TVs. In addition to the loudspeaker outputs, the C 700 V2 has a subwoofer output jack. Using the BluOS Controller app you can set the crossover point for a seamless blend between the subwoofer and main speakers.

The C 700 V2 features two-way aptX HD Bluetooth, so you can listen to music through wireless headphones, and stream audio from any smart device. NAD offers software tools that allow the C 700 V2 to be integrated into smart home control systems from Control4, Crestron, Elan, RTI, and others. This allows you to integrate your music playback with the other smart functionality of your connected home, including lighting, shades, HVAC, and security. The C 700 V2 is also certified Roon Ready, so you can stream music from a Roon Core server.

LEGENDARY VALUE

The NAD C 700 V2 BluOS Streaming Amplifier is a compact, stylish, all-in-one solution, designed with today's connected music lovers in mind. Small but mighty, it will thrill listeners with its effortless, dynamic sound. Out of the box, it can play music from a huge range of local, network-attached, and cloud-based sources. And with its digital and analogue inputs, the C 700 V2 plays nicely with legacy components.

The C 700 V2 can be used as a standalone music system or it can be integrated into a BluOS whole-home music system with as many as 63 additional zones, with full support for high-resolution audio. It can also be combined with other AirPlay 2 components for whole-home music. Ever since NAD introduced the legendary 3020 integrated amplifier in 1978, the NAD brand has been renowned for value, performance, simplicity and innovation. With the C 700 V2 BluOS Streaming Amplifier, NAD has completely updated that tradition for the streaming era.

All specs are measured according to IHF 202 CEA 490-AR-2008 standard. THD is measured using AP AUX 0025 passive filter and AES 17 active filter.

GENERAL SPECIFICATIONS

Continuous output power into 8/4 ohms	>80W/ 100W (20Hz-20KHz at rated THD+N, both channels driven)
THD+N (20 Hz – 20 kHz)	<0.04% (250mW to 90W, 4 ohms)
Signal-to-Noise Ratio	>84dB(A-weighted,500mV input,ref.1W out in 8 ohms)
Clipping power	>86W(at 1KHz 0.1% THD 8Rx2CH) >102W(at 1KHz 0.1% THD)
IHF dynamic power	8 ohms: 100W - 4 ohms 125W
Damping factor	>90 (ref.8 ohms,20Hz-20KHz)
Frequency response	±0.18dB(20Hz-20KHz)
Tone Controls	Treble: ±6.0dB at 20KHz - Bass: ±6.0dB at 60Hz
Channel separation	>93dB(1KHz) - >72dB(10KHz)
Input sensitivity (for 100 W in 8 ohms)	Line In: 550mV Digital In: -12%FS
Standby power	<0.5W

SUBWOOFER OUT

Maximum output level	4.0 Vrms (ref 0.0032% THD+N 100 Hz)
Signal-to-Noise ratio	>106 dB (20 Hz-20 Hz, ref 1V out)
THD+N	<0.006 % (20 Hz-200 Hz, ref 1.964V)
Output impedance	600 ohms

BLUOS

AUDIO

Supported audio file format	https://support.bluos.net/hc/en-us/articles/360000191327-What-Formats-are-Supported-by-BluOs
Sampling rate	up to 192kHz PCM
Bit depths	16 – 24

CONNECTIVITY

3rd Party integrations	Airplay 2
Network connectivity	Gigabit Ethernet RJ45 Wi-Fi 5
USB	1 x Type-A port for connection to USB memory stick (FAT32 or NTFS formatted) and supported peripherals
Bluetooth quality	aptX HD
Bluetooth connectivity	Two-Way (Receive and Headphone modes)

USER INTERFACE

Supported operating system*	Music playback from network shares on the following desktop operating systems: Microsoft Windows XP, 2000, Vista, 7, 8 to current Windows Operating Systems and macOS versions
Mobile Application	Free BluOS Controller App available for download from the respective App stores of Apple iOS devices (iPad, iPhone and iPod), Android devices, Kindle Fire and Windows or macOS desktops

SUPPORTED SERVICES

Supported Radio, Music Services, Integration and Digital Assistants	https://support.bluos.net/hc/en-us/articles/360000199908-What-Music-Services-does-BluOS-Support-
---	---

DIMENSION AND WEIGHT

Gross dimensions (W x H x D)**	218 x 96 x 266 mm 8 5/8 x 3 13/16 x 10 1/2 inches
Net weight	4.8 kg (10.6 lbs)
Shipping weight	5.3 kg (11.7 lbs)

* Some features available via a future software update

** Gross dimension includes feet, extended front and rear panel terminals

Specifications are subject to change without notice. Check out www.NADelectronics.com for updated documentation or latest information about C 700 V2.



NAD Electronics International reserves the right to change specifications or features without notice. NAD is a registered trademark of NAD Electronics International. All rights reserved. No part of this publication may be reproduced, stored, or transmitted in any form whatsoever without the written permission of NAD Electronics International. © 06/24 24-029 NAD Electronics International. www.NADelectronics.com