



Audio

Frequency response 40Hz - 22kHz
Tweeter Custom 20mm silk dome
Woofer 85mm treated natural fibre cone
Amplifier 2 x 25W BTL class D
Cabinet 2-way bass reflex tuned to 68Hz
Internal cabinet volume 2.0 litres
Crossover frequency 2.5kHz
Digital to analogue 104dB 24-bit/192kHz DAC

Connectivity

Bluetooth V5.1, aptX HD, SBC, AAC, BLE, A2DP
MM phono in Stereo RCA (max 7mV)
Aux in 3.5mm combined jack (max 2.3Vrms)
Optical in 3.5mm combined jack (TOSLINK 24-bit/192kHz PCM)
USB audio in 24-bit/96kHz UAC 1.0
Sub out Full-frequency mono RCA (max 2.0Vrms)
Left speaker connector 3.5mm mono jack

Features

Snooze mode 20 min auto-standby and wake-up
Adjustable input levels Aux, phono, optical

General Specifications

Finishes Rich walnut veneer or charcoal lacquer with dark slate woven fabric grille
Box contains Left speaker, right speaker, AC power adapter, 3m high purity speaker interconnect cable, remote control with battery (CR2025), quick start guide
Power adapter 100-240V~50-60Hz input 18VDC 2.8A output, 1.8m cable, 2.1 x 5.5mm DC plug
Power consumption 0.5W standby, 7W typical
Product dimensions
 H185 x W135 x D155mm (cabinet)
 H202 x W135 x D165mm (max)
Product weight 2.2kg each
Inner carton dimensions W400 x D185 x H285mm
Packaged weight 5.1kg (pair)
Shipping carton dimensions W570 x D410 x H320mm
Shipping carton weight 1.1kg
Gross weight 16.4kg (box of 3 pairs)
Rich Walnut product code/EAN
 MR1C-WAL / 5060637250365
Charcoal lacquer product code/EAN
 MR1C-CHR / 5060637250372